

SPECIFICATIONS

ARTICLE

Designation : **Adhesive glass fabric**

Code bobet : *See table below*

Selling Unit : **Meter**



Non-contractual pictures

CHARACTERISTICS

HIGH TEMPERATURE ADHESIVE FABRIC

- PTFE (polytetrafluoroethylene) coated glass fabric liner
- Provided with an adhesive strip (silicone polymer)
- Non-stick, very good slip coefficient
- Easy to clean
- Resists to temperatures from -70°C to +260°C continuously, and +315°C in peak
- Self extinguishing
- Outstanding dimensional stability
- Temperature and pressure have no noticeable effect and no creep
- Odourless and tasteless
- Can be in contact with foodstuffs
- Excellent resistance to friction
- Supplied in 30-meter rolls

APPLICATION :

Welding machines, shrink-wrapping machines, hoppers coatings...

Width (mm)	Nominal thickness (mm)	Code Bobet
10	0.13	3541
15	0.13	3542
20	0.13	3543
25	0.13	3544
30	0.13	3545
40	0.13	3546
50	0.13	3547
60	0.13	3548
70	0.13	3549
80	0.13	3550
90	0.13	3551

Width (mm)	Nominal thickness (mm)	Code Bobet
100	0.13	3552
1000	0.13	3566
15	0.25	3554
20	0.25	3555
25	0.25	3556
30	0.25	3557
40	0.25	3558
50	0.25	3559
60	0.25	3560
70	0.25	3561

