

SPECIFICATIONS



ARTICLE

Designation : **ASCEND shoe S3**

Code bobet :

15298 : S.38 | 15303 : S.43

15299 : S.39 | 15304 : S.44

15300 : S.40 | 15305 : S.45

15301 : S.41 | 15306 : S.46

15302 : S.42 | 15307 : S.47

Selling Unit : **pair**

Non-contractual pictures



CHARACTERISTICS



- Full grain water resistant leather.
- Lightweight shoe with modern design.
- AirToe Composite perforated safety toe cap with breathable membrane.
- Save & Flex "no-metal" puncture resistant midsole. Removable Action Dry sole made of active carbons felt.
- Last : Natural Confort 11 Mondopoint.
- SRC grip coefficient :
 - * Ceramic / water-detergent SRA : 0.45 flat shoe and 0.32 shoe inclined toward heel (7°)
 - * Steel/glycerin SRB : 0.44 flat shoe and 0.21 shoe inclined toward heel (7°)

DESCRIPTION :

- Upper :**
- Upper leather : black full grain water resistant leather 1.8/2.2 mm.
 - Tab : stress out.
 - Lining : Wingtex.
 - Laces : Nylon, abrasion resistance (>15000 cycles under 250g according to DIN 4843).

- Sole :**
- Assembly : strobel.
 - Sole : Polyurethane.
 - Comfort density : 0.50
 - Outsole: PU

STANDARDS :

In compliance with the European Regulation UE 2016/425 on personal protective equipment

In compliance with the European EN ISO 20345:2011 S3 SRC

With safety toe cap

S3 : Fundamental requirements + closed rear + anti-static + energy absorption in the heel + resistance to hydrocarbons + perforation resistance + material for water-repellent upper + studded outsole

SRC : Outsole slip resistance on ceramic and steel

Weight (Size 42) : 1.31 Kg / pair

