

SPECIFICATIONS

ARTICLE

Designation : **Stainless steel caster with central hole**

Code bobet :

15084 : D. 100 SW

15085 : D. 100 SW BR

15493 : D. 125 SW

20650 : D. 125 SW BR

Selling Unit : **Unit**

Non-contractual pictures

**CHARACTERISTICS****FRAME :**

- Swivel caster with double blocking system for the version with brake
- Stainless steel housing
- Double ball bearing swivel head
- Wheel axle with nut

WHEEL :

- Body : polypropylene
- Tread : non staining grey rubber, thermoplastic - Hardness : 87 Shore A
- Smooth hub, stainless steel brace
- Fixing by the central hole

Temperature : -20°C to +60°C

In compliance with the standard EN12530

N.B. : this caster is also available with a diameter 75 : Code 17812 (without brake) and 17813 (with brake)

Details	Wheel Diameter	Tread width	Diameter central hole	Offset	Total height	Dynamic load capacity	Static load capacity	Weight	Code
Without brake	100 mm	32 mm	13 mm	38 mm	135 mm	80 kg	160 kg	0,490 kg	15084
Brake	100 mm	32 mm	13 mm	43.5 mm	135 mm	80 kg	160 kg	0,660 kg	15085
Without brake	125 mm	32 mm	13 mm	41 mm	160 mm	100 kg	200 kg	0,590 kg	15493
Frein	125 mm	32 mm	13 mm	41 mm	160 mm	100 kg	200 kg	0.750 kg	20650