

SPECIFICATIONS

ARTICLE <u>Designation</u> : Stainless steel caster with plate and blue wheel BB <u>Code bobet</u> : 20934 : D.100 F 20935 : D.100 SW 24638 <u>Selling Unit</u> : Unit <i>Non-contractual pictures</i>	
---	---

CHARACTERISTICS

FRAME :

- Stainless steel axle
- Axle made of a stainless steel AISI 304 brace, a stainless steel screw in compliance with the standard UNI EN24017 and a stainless steel nut in compliance with the standard UNI EN24032

WHEEL TYPE :

- Soft polyurethane tread - Polyamide 6 body - Hardness 85 SHORE D
- Central ball bearing
- For medium loading
- Easy push, reduced effort
- Eases handling of the trolley
- Ideal for all kind of sectors
- Replaces standard nylon and rubber casters
- Universal : Recommended for all types of floors

- Temperature : -10°C to +70°C

Details	Wheel Diameter	Tread width	Sun Int. Platinum	Axis dimension between mounting	Diameter holes	Total height	Dynamic load capacity	Weight	Code
Fixed	100 mm	30 mm	100 x 85 mm	80 x 60 mm	9 mm	128 mm	120 kg	0.53 kg	2093
Swivel	100 mm	30 mm	100 x 85 mm	80 x 60 mm	9 mm	128 mm	120 kg	0.67 kg	2093
Pivotante avec frein	100 mm	30 mm	100 x 85 mm	80 x 60 mm	9 mm	128 mm	120 kg		2463