

SPECIFICATIONS

ARTICLE

Designation : **Stainless steel caster with plate D.125 and D.200**

Code bobet :

13009 : D.125, F H.155

13008 : D.125, SW H.155

30200 : D.125, SW H.240

Selling Unit : **Unit**

Non-contractual pictures



CHARACTERISTICS

TYPE OF FRAME:

- Stainless-steel yoke, pivot on double row of balls for the swivel version
- Bolted wheel axle

WHEEL TYPE:

- Wheel body: polypropylene
- Bandage:
 - * Code 13009: hardness 75 Shore D
 - * Code 13008: hardness 65 Shore D
 - * Code 30200: hardness 75 Shore D
- Smooth hub
- Plate fixing

Mini / maximum temperature: -20 to +60 ° C for codes 13008 and 13009; -40/+80 ° C for code 30200

Complies with the standard EN 12532

Details	Wheel Diameter	Tread width	Dimension platinum	Distance between axis	Height of wheel	Offset	Ray space	Dynamic load capacity	Static load capacity	Weight	Code
Fixed	125 mm	40 mm	102 x 87 mm	80 x 60 mm	155 mm			200 kg	400 kg	0.54 kg	13009
Swivel	125 mm	40 mm	105 x 85 mm	80 x 60 mm	155 mm	38 mm	100.5 mm	200 kg	400 kg	0.65 kg	13008
Swivel	200 mm	52 mm	135 x 105 mm	105 x 80 mm	240 mm	52 mm	152 mm	400 kg	800 kg	1.72 kg	30200