

# SPECIFICATIONS

**ARTICLE**

Designation : **Coupler air hosetail with button DN6 ISO B**

Code bobet :

**24607 : DN6, Connection D6**

**24608 : DN6, Connection D8**

**24609 : DN6, Connection D10**

Selling Unit : **Unit**

*Non-contractual pictures*

**CHARACTERISTICS**

DN6 ringed socket fitting coupler

- Automatic push-button purge
- Maximum operating pressure : 12 Bar
- Operating temperature : -20°C to +100°C (NBR)
- Flow rate : 675 l/min

**COMPOSITION**

- Coupler : Black anodized aluminum, nickel-plated brass
- Tip : Nickel-plated steel
- Gasket: NBR
- ISO B
- Silicone-free
- Long-term reliability
- Flexibility : Adjustable for easy assembly and disassembly
- Identification : Profile marked on the body of the coupler to avoid damage caused by poor connection
- Robustness and lightness

**ADVANTAGES :**

Easy to use and ergonomic in order to provide intuitive and effortless one-handed operation

Suitable for use with all kind of compressed air networks, and all industries

Connection to pneumatic tools, blow guns, special machines, assembly lines

**SAFETY**

- No involuntary disconnection or whiplash effect to avoid the risk of accidents at work
- 2 presses of the button with 2 disconnection stages: 1. Automatic purge - 2. Disconnection