

SPECIFICATIONS

martor**ARTICLE****Designation : Secunorm 610 detectable cutter****Code bobet : 24673****Selling Unit : Unit**

Non-contractual pictures

CHARACTERISTICS

PARTICULARLY RESISTANT TO CLOGGING SAFETY KNIFE WITH SEMI-AUTOMATIC BLADE RETRACTION

FEATURES :

- High security
- Tool-free blade change
- Extremely abrasion resistant
- Particularly ergonomic
- Lockdown
- Special rounded blade
- Ambidextrous
- For extreme demands
- Metal detectable: Identifiable by X-ray detector
- Fixing eyelet

DIMENSIONS: 158 x 27 x 76 mm**WEIGHT:** 139.0 g**BASE MATERIAL:** ALUMINUM**BODY:** ALUMINUM**CUTTING DEPTH:** 32 mm**COMPATIBLE BLADE:**

* Code 24674: Special rounded stainless steel blade. Sharpening on 2 sides

Dimensions: L. 66.5 x H. 18.9 mm x D. 0.63 mm Weight: 4.7 g

Packaged in a case of 5 blades

Storekeepers, Receivers, Handlers...


Main materials that can be cut: cardboard (up to 3 corrugations), bags, stretch film, heat shrink, strips of film and paper, plastic strapping, hidden and laminated film, synthetic foam, polystyrene, wire, string,

adhesive, textile, felt, canvas...

STANDARDS :

Patented model, GS certificate No. 187356-7897-55094-2023

CHANGEMENT DE LAME



Tirer la sécurité **complètement** vers l'extérieur ...



...et faire pivoter la gâchette **complètement** hors de la poignée.



Dégager le ressort de la rainure en exerçant une **légère pression** et le pousser de côté. Changer la lame et la replacer avec **précision** sur les ergots.

BLADE CHANGE



Fully pull out the lock...



...and unfold the handle completely.



Release the spring from the groove by applying **light pressure** and by pressing it to the side. Change the blade and put the replacement **precisely** on the location lobes.