

SPECIFICATIONS

ARTICLE

Designation : **Female nipple**

Code bobet :

514 : 15 x 21 mm

515 : 20 x 27 mm

516 : 26 x 34 mm

Selling Unit : **Unit**

Non-contractual pictures



CHARACTERISTICS

	DN	C	E	G	L	kg
	12	G1/2	11	24	31,5	0,031
		G3/4	11	30	38	0,058
		G1	11	36	36,5	0,058

Female nipple, BSPP (British Standard Pipe) cylindrical

- Suitable for many applications for water and compressed air.
- Complies with national and international standards which allows interchangeability with many global manufacturers.

TECHNICAL CHARACTERISTICS :

- Usable fluids: compressed air, water, as well as all fluids compatible with the constituent materials.
- Operating temperature: from -20°C to + 100°C: these temperature limits can be modified by the type of use (type of fluid, service environment, etc.).
- Constituent material: nickel-plated brass
- Maximum operating pressure: 20 bars
- Flow rate: 2200 NI/min
- Passage: 12 mm
- BSP thread:
 - * Code Bobet 514: 15 x 21 mm = G1/2
 - * Code Bobet 515: 20 x 27 mm = G3/4
 - * Code Bobet 516: 26 x 34 mm = G1"

ⓘ

They depend essentially on the nature and the thickness of the tube, on the ambient temperature and on that of the fluid conveyed, on the nature of the constituent materials.