

SPECIFICATIONS

ARTICLE

Designation : **Fixed housing in stainless steel with plate**

Code bobet :

158 : Diam. 80 mm

159 : Diam. 100 mm

160 : Diam. 125 mm SP

161 : Diam. 160 mm

162 : Diam. 200 mm

Selling Unit : **Unit**

Non-contractual pictures



CHARACTERISTICS

Fixed housing with plate

(SP = small plate and LP = large plate)

- Frame : stainless steel AISI 304 plate and housing, resistant to corrosion
- Central axle integrated on plate, cold riveted
- Compatible with NYLTEC wheels
- This type of housing is adapted for applications exposed to low loads (max.300kg), adapted in wet and corrosive areas.

Details	Height with wheels	Sun Int. Platinum	Axis dimension between mounting	Entrefourche	Rated load capacity	Code
For wheel D.80	108 mm	85 x 100 mm	80 x 60 mm	40 mm	200 kg	158
For wheel D.100	129 mm	85 x 100 mm	80 x 60 mm	45 mm	200 kg	159
For wheel D.125	157 mm	85 x 100 mm	80 x 60 mm	45 mm	220 kg	160
For wheel D.160	199 mm	113 x 140 mm	105 x 85 mm	60 mm	300 kg	161
For wheel D.200	241 mm	114x 140 mm	105 x 85 mm	60 mm	300 kg	162