

SPECIFICATIONS

ARTICLEDesignation : **Non adhesive glass fabric**Code bobet : **3565 : thickness 0.13**Selling Unit : **Meter**

Non-contractual pictures

CHARACTERISTICS

- Non adhesive glass fabric, PTFE (polytetrafluoroethylene) coated
- Coating perfectly uniform
- Resistant to temperatures from -73°C to +260°C continuously, and +315°C occasionally
- Sold by meter

BENEFITS :

- Antiblock, very good slip coefficient
- Odourless and tasteless : can be in contact with foodstuffs
- Thanks to its chemical inertia, PTFE can not be attacked by any chemicals such as acid, salt, solvent, except fluorites (CaF₂) and trifluorines at high temperatures and under high pressure, as well as sodium (Na) and molten potassium (K), and products which attack glass
- Arc resistance over 300 seconds
- Lower loss factor of $2 \cdot 10^{-4}$ à 60Hz, 1Hz, 10 6Hz
- Dielectric constant 2.1 at 60Hz, 1KHz, 10 6Hz

STANDARDS :

In compliance with the EU 10/2011 regulation related to materials and items in plastic in contact with foodstuffs

APPLICATION :

- Can be mainly used for : hoppers coatings, protection curtain for heating tunnel, heat seal, lining of weighing scales, isolation of laminations,...

Weight Rating (grammes/M ²)	Width (mm)	Nominal thickness (mm)	Breaking Point	Share PTFE	Breakdown voltage	Code Bobet
235	1000	0.13	28 KGF/cm	54%	23.62 kv/mm	3565

