

# SPECIFICATIONS

**ARTICLE**

Designation : **Torro hose clip**

Code bobet : *See table below*

Selling Unit : **Hundred**

*Non-contractual pictures*

**CHARACTERISTICS**

WORM DRIVE HOSE CLIP, MULTI-PURPOSE

- Hose clip with tangent screw, width 9 or 13 mm
- Asymmetric housing : it prevents any tipping, thanks to the support remote from the screw head when tightened.
- Crown of screw : it takes the band end away from the screw head when tightened.
- Housing : Made without welds or rivets, it hugs the inner face of the belt, to obtain regular contact pressure over the entire circumference.
- Plain band : pressed and moulded, with rounded and raised edges, it avoids any risk of deterioration of the hose.

Material(band, screw and housing) : stainless steel 304 (AISI 1.4301)

=> corrosion resistance in salt spray tasting : Min. 400h

Coating of locking components without chrome VI

Clamping ranges in accordance with DIN 3017

**APPLICATION :**

APPLICATION DOMAIN :

In all industrial and automotive sectors.

It is intended for all types of connections on water, air and fuel circuits for which a hose/fitting junction of extreme safety and reliability is necessary.

Example:

Connection for cooling system

- Fuel fill and bleed supply lines

whether under pressure

- Oil lines
- Pipes for sanitary applications
- Machine building
- Connections for construction of household appliances
- Flexible lines for the commercial vehicle industries...

Band width (mm)	Clamping range	Code Bobet
9	8-16	445
9	12-22	446

Band width (mm)	Clamping range	Code Bobet
9	16-27	447
9	20-32	448
9	25-40	449
9	32-50	450
9	40-60	8388
13	16-27	451
13	20-32	452
13	25-40	453
13	32-50	454
13	40-60	455
13	50-70	456
13	70-90	458
13	110-130	462
13	90-110	460
13	120-140	463