



SPECIFICATIONS

ARTICLE

Designation : **Isoclean crimped hose D.12**

Code bobet :

18927 : Diam.12 / crown 25 m

19032 : Diam. 12/ crown 33 m

Selling Unit : **Unit**



Non-contractual pictures

CHARACTERISTICS



INDUSTRIAL WASHING HOSE MEDIUM PRESSURE - CRIMPED

- Stainless steel crimped couplings :
 - * On one end, fixed male coupling 15x21
 - * On the other end, fixed male coupling 15x21

CHARACTERISTICS

- Inside Diameter : 12 mm
- Outside Diameter : 22 mm
- Weight : 0,325 g/m
- Hose thickness : 5 mm
- Working pressure : 80 bars
- Temperature : -20°C (80 bar) / +70°C (50 bar)

BENEFITS

The properties of the materials making up this pipe make it a high-performance, safe and reliable pipe, enabling it to meet strict specifications

USES

APPLICATION:

- * Industrial washing: terminal use on installations with centralized network, ideal for washing stations

SECTORS OF ACTIVITY: Food industries, slaughterhouses, communities, traders, artisans, etc.

ALIMENTARITY :

The supplier certifies that this hose, designed for food contact, complies with EU Regulation 10/2011 and has been phthalate-free since July 1, 2008.



ENVIRONMENTAL CHARACTERISTICS

Isoclean crimped hose D.12

BOBET codes : 18927, 19032

The environmental impacts of this product have been analyzed throughout its life cycle.

