

SPECIFICATIONS

ARTICLE

Designation : **THERMIDOR hose**

Code bobet :

9121 : Diam.15 / length 25 m | 213 : Diam.19 / length 50 m

212 : Diam.15 / length 50 m | 9123 : Diam.25 / length 25 m

9122 : Diam.19 / length 25 m | 214 : Diam.25 / length 50 m

Selling Unit : **Meter**

Non-contractual pictures



CHARACTERISTICS



The Thermidor water hose is the product for universal use. It suits for mobile or fixed pipe systems in industries, construction, agriculture, landscape gardeners, municipalities, public parks... Moreover, it is flexible, tough and easy to use.

DESCRIPTION

- Black, non porous, smooth, EPDM tube and coating
- Working pressure : 15 bars
- Temperature from -20°C to +100°C
- Insertions : synthetic lining
- High flexibility, soft and resistant to curvature
- Resistant to ozone and climate
- Unbreakable and non fat
- Marking : 6 yellow axial stripes on black background

Inner diameter (mm)	Work pressure (bar)	Minimum pressure burst (bar)	Wall thickness (mm)	Bend radius (mm)	Weight (Kg/m)
15	15	45	3	150	0.28
19	15	45	3.5	190	0.39
25	15	45	4	250	0.55