

SPECIFICATIONS

ARTICLE

<u>Designation</u>: Stainless steel hydrualic stuffer 25 liters


Code bobet : 20693 Selling Unit : Unit





Non-contractual pictures

CHARACTERISTICS



Dimensions	
Α	660
В	500
С	1148
D	497
Е	1103

Its design, finish and the quality of the materials used give it exceptional longevity and reliability.

- Double-tightened stainless steel lid fitted with an O-ring to prevent any risk of flesh leaking.
- Independent hydraulic unit, closed circuit, with stainless steel tank. This system has many advantages: the oil is not polluted, regular oil change is therefore no longer essential, the pump is preserved, and its lifespan extended, the operating silence is increased. Finally, the machine will be delivered with a full tank of oil, after which it can be moved and washed with plenty of water without any problem.
- Stainless steel piston, fitted with a removable O-ring, which is coupled to the cylinder rod via a stainless steel end piece.
- Handle on the front, allowing the dual function of protecting the control and movement devices.
- Two wheels and two adjustable feet make it easy to move around.

TECHNICAL CHARACTERISTICS

Capacity: 25 litersCapacity: 20 kg

- Size: L. 500 x l. 660 x H. 1148 mm- Height turbinate (cannula): 1103 mm

- Weight: 137.5 kg

Voltage: 400 V tri - 50 HzOil tank capacity: 9 litersMotor power: 0.75 Kw - 1 CV

- Standard equipment: 3 cones (cannulas): 14, 20 and 33 mm



REGULATIONS:

Complies with the following European directives:

- Machinery Directive 2006/42/EC
- EMC Directive 2014/30/EU
- LV Directive 2014/35/EU

