

SPECIFICATIONS

ARTICLE

Designation : **HYFLEX® 11561 glove**

Code bobet :

23887 : S.7

23888 : S.8

23889 : S.9

23890 : S.10

23891 : S.11

Selling Unit : **pair**

Non-contractual pictures



CHARACTERISTICS



Ansell Earth

- The INTERCEPT™ yarn provides high cut protection while providing dexterity and comfort.
- The palm coating design improves grip, extends glove life in abrasive conditions and allows the hand to breathe.
- Fiber glass free
- Antistatic
- Suitable with touchscreens



Color : Grey
 Finishing: Palm Coated
 Coating material : Nitrile
 Liner Material : Nylon, HPPE, Basalt, Spandex, Polyester
 Cuff Style : Knitwrist, gauge 15, length 230-275mm

PERFORMANCES :

- HyFlex 11-561 is the best choice when high cut and dexterity in dry to light oil conditions are needed.
- The thin coating uses FORTIX technology which provides not only extra durability but also a fit that is more comfortable and breathable.
- The reinforced thumb crotch increases protection for a key area of hand contact and extends the lifetime of the glove.
- High cut protection (ISO C/ANSI A3) and tear resistance

WASHING TEMPERATURE: 40°C

APPLICATIONS :

- Handling metal sheets & panels
- Handling parts with sharp, rough edges
- Final assembly
- Handling materials with sharp or rough edges
- Handling the cutter blade / in the skinning machine

PACKAGING :

12 pairs / paper band
 carton of 144 pairs = 12 x 12 pairs

STANDARDS :

Complies with EU regulation 2016/425 relating to personal protective equipment (Category II)


Complies with European standards:

- General requirements: EN ISO 21420:2020
- Mechanical risks: EN388:2016 + A1:2018 4X42C
- Thermal risk : EN407:2004 (X1XXXX)

Complies with the decree of August 5, 2020, relating to rubber materials and objects intended to come into contact with foodstuffs.



EN ISO 21420 :
2020 Cat.II



EN388:2016 + A1:
2018 - 4X42C



EN 407 : 2020
X1XXXX

HyFlex® 11-561

FICHE D'INFORMATION SUR LA DURABILITÉ DES PRODUITS



ANSELL EARTH

Ansell Earth représente nos produits qui offrent des avantages environnementaux tout au long de leur cycle de vie.

Production

Fabriquée dans une usine :

- fonctionnant à 83% d'énergie renouvelable
- certifiée par Intertek pour avoir détourné >99% des déchets de la décharge
- dotée d'un système de gestion de l'environnement accrédité

Conditionnement

- La boîte en carton contient min. 45% de matériaux recyclés
- Taille des cartons optimisée pour une expédition efficace

Production

Fabriquée dans une usine :

83%

fonctionnant à 83% d'énergie renouvelable ¹

De la biomasse



> 99%

certifiée par Intertek pour avoir détourné >99% des déchets de la décharge ²



dotée d'un système de gestion de l'environnement accrédité ³

Certifié ISO 14001:2015 par SGS



Conditionnement

min. 45%

La boîte en carton contient min. 45% de matériaux recyclés ⁴



Taille des cartons optimisée pour une expédition efficace ⁵

