

SPECIFICATIONS

**ARTICLE**

Designation : **Matador® HVS 3000 slaughtering pistol**

Code bobet : **24798**

Selling Unit : **Unit**

Non-contractual pictures

**CHARACTERISTICS**

NEW MODEL WITH:

- PATENTED LOCKING SYSTEM and ERGONOMIC HANDLE
- QUICK PIN PROMOTING RESPECT FOR ANIMAL WELFARE EVEN ON LARGE ANIMALS
- EASY MAINTENANCE
- FACILITATES THE OPERATOR'S WORK, AUTOMATIC EXTRACTION OF THE CHARGE

The MATADOR® is a captive pin slaughter gun using 27 caliber pyrotechnic charges. It is used when slaughtering animals such as large cattle and exceptional beasts as well as calves, cows and sheep. It is composed of a barrel and a handle connected by a hinge clevis.

Length: 310 mm

Pin length: 90 mm

Pin diameter: 12 mm

Diameter: d.60 mm

Weight: 2.72 kg

Material: Steel

Locking: Ball

Loads (cartridges): MATADOR® caliber 27 yellow, red, black (see paragraph LOADS)

Maximum authorized rate: 30 shots/hour

Maximum number of shots: 40,000 shots

Maximum lifespan: 3 years

For any other information, see the product instructions.

CARTRIDGES :

Loads to use:

- BLACK LOADS:

- * Bobet code 24204 = box of 500
- * Reserved for large cattle weighing over 700 kg: bulls, exceptional animals, young cattle

- RED LOADS:

- * Bobet code 24205 = box of 500

Standard model for general use for cows, calves, heifers and horses

- YELLOW LOADS:

- * Bobet code 24203 = box of 500
- * Recommended for the slaughter of animals weighing less than 250 kg: sheep and goats

SAFETY AND MAINTENANCE :

- You must have at least 2 pistols at the felling site. Any pistol that is defective or showing signs of malfunction must be replaced immediately

WARNING: Never remove by hand a poorly exploded charge, engaged in the barrel

Never point the pistol at yourself or at another person even if the pistol is not loaded

MAINTENANCE :

- Optional (sold separately): Tool kit for maintenance of this gun

IMPORTANT :

The components of the felling gun, like the charges, being an integral part of the device, only those studied, checked, supplied or recommended by us must be used in our LE MATADOR® felling guns (Interministerial decree of April 10, 1981 - J.O. of April 17, 1981 - chap. II - Art. 7 and chap IV - Art. 9 relating to the approvals and conditions of use of this equipment). Any deviation from the requirements of the text of this decree, like all the instructions for use of this equipment, will engage, in the event of an accident, the responsibility of those who take the initiative.

STANDARDS :

Complies with:

- European Machinery Directive 2006/42/EC
- Animal Welfare Regulation EC 2009/1099
- Standard EN 15895 on portable propellant-charge tools
- General principles on machine safety EN ISO 12100



Repère	Désignation	Qte	Code TERMET	Code BOBET
1	Anneau embout poignée	1	5907	21172
2	Embout	1	16	21171
3	Ressort marteau	1	21	7361
4	Ressort taquet	1	5795	20995
5	Taquet	1	18	10642
6	Ressort verrouillage	1	3695	15642
7	Porte culot trèfle	1	10647	24802
8	Axe d'accouplement	2	34	7371
9	Cordon d'armement	1	41	7381
10	Marteau	1	19	7360
11	Poignée	1	3705	15640
12	Goupille	2	26	10644
13	Percuteur	1	24	7363
14	Bille de verrouillage	1	3698	15648
15	Chape de basculement	1	32	10647
16	Jonc de verrou	1	29	7369
17	Bague	1	10443	24805
18	Canon verrou	1	10685	24804
19	Joint de blocage	1	40	7380
20	Jonc tête de broche	1	30	7375
21	Broche HVS	1	11609	24799
22	Rondelle protection arrière bleu	1	1269	12417
23	Rondelle protection arrière brun	1	38	7377
24	Anneau élastomère (sachet de 11 pces)	1	9182	24855
25	Rondelle protection avant	2	39	7378
26	Disque étanchéité	1	65	7376
27	Rallonge HVS	1	11798	24797

