

SPECIFICATIONS



ARTICLE

Designation : **MISTRAL shoe S1P**

Code bobet :

15798 : S.38 | 15803 : S.43

15799 : S.39 | 15804 : S.44

15800 : S.40 | 15805 : S.45

15801 : S.41 | 15806 : S.46

15802 : S.42 | 15807 : S.47

Selling Unit : **pair**

Non-contractual pictures



CHARACTERISTICS



- Lightweight shoe with modern design.
- AirToe Aluminum perforated safety toe cap with breathable membrane.
- WOW2 Removable antifatigue sole, wedge sole with a shape memory that equally distributes weight over the foot.
- SRC grip coefficient :
 - * Ceramic / water-detergent SRA : 0.45 flat shoe and 0.32 shoe inclined toward heel (7°)
 - * Steel/glycerin SRB : 0.44 flat shoe and 0.21 shoe inclined toward heel (7°)

DESCRIPTION :

Upper : - Blue suede leather soft, breathable and perforated
 - Lining : Wingtex® air tunnel

Sole : - Comfort sole : Polyurethane flexible expanded
 - Comfort density : 0.50
 - Outsole : Abrasion resistant compact PU antistatic, anti slip and oil resistant.
 - Anti-perforation midsole.

STANDARDS :

In compliance with the European Regulation UE 2016/425 on personal protective equipment.

In compliance with the European EN ISO 20345:2011 S1P SRC

S1P : Fundamental requirements + closed rear + anti-static + energy absorption in the heel + resistance to hydrocarbons + PERFORATION RESISTANCE (P)

SRC : Outsole slip resistance on ceramic and steel

In compliance with the european standard : EN ISO 61340-4-3:2001 = ESD : load-dissipating shoes electrostatic

Weight (Size 42) : 1 Kg / pair

