

SPECIFICATIONS

ARTICLEDesignation : **NLOCK white flat shoe S2**

Code bobet :

27235 : S35 | 27740 : S40 | 27745 : S45**27236 : S36 | 27741 : S41 | 27746 : S46****27737 : S37 | 27742 : S42 | 27747 : S47****27738 : S38 | 27743 : S43 | 27748 : S48****27739 : S39 | 27744 : S44**Selling Unit : **pair**

Non-contractual pictures

**CHARACTERISTICS**

Food processing moccasin with safety toecap

Designed for everyday efficiency, the NLOCK combines protection and ease of use.

Its FitNLock dial closure allows for quick fitting and optimal support, without compromising on comfort.

Made of smooth, lightweight, and easy-to-clean microfiber, it meets the demands of environments such as catering and food processing.

Discreet composite toecap and anti-slip DualTech sole for enhanced safety.

- UPPER: Easy-to-clean smooth microfiber
- CLOSURE: Dial closure system + protective tongue for optimal foot support.
- LINING: Breathable, very soft, and comfortable mesh lining (GRS certified)
- INSOLE: Removable PU and textile mesh
- OUTSOLE: Injected dual-density PU sole, SR anti-slip. Antistatic, and resistant to oils and acids
- TOE CAP: Composite impact resistant to 200 joules
- COLOR: White
- WEIGHT (size 42): 590 grams

COEFFICIENT OF TRACTION

BASE (A & B): 0.39 (Heel to Toe) and 0.41 (Toe to Heel)

SR (C & D): 0.27 (Heel to Toe) and 0.32 (Toe to Heel)

CARE INSTRUCTIONS

- Machine washable at a maximum of 30°C
- 15-minute cycle

USES

Hygiene and institutional use, food processing and catering, light industry...

STANDARDS :

Compliant with Regulation 2016/425 on PPE (Personal Protective Equipment)

Compliant with EN ISO 20345:2022 Safety Footwear - S2 SR ESD

S2: Basic requirements + Closed backs + Antistatic properties + Heel energy absorption + Water resistance (upper materials)

SR: Slip resistance (ceramic floor + oil)

ESD: Dissipation of electrostatic charges

