

SPECIFICATIONS

ARTICLE

<u>Designation</u>: Non-slip rubber overshoes

Code bobet:

24591 : S.S (34-36) 24592 : S.M (37-40) 24593 : S.L (41-44) 24594 : S.XL (45-48)

<u>Selling Unit</u>: **pair** *Non-contractual pictures*



CHARACTERISTICS

Surface	Sol carrelé (SRA) Laurylsulfate de sodium (NaLS)		Sol acier (SRB) Glycérine	
Lubrifiant				
Position du pied	À plat vers l'avant	Du talon vers l'avant	À plat vers l'avant	Du talon vers l'avant
Exigences de la norme	≥ 0.32	≥ 0.28	≥ 0.18	≥ 0.13
Cœff. d'adhérence (42)	0.54	0.38	0.62	0.22

Black EASY-GRIP non-slip overshoes

Composition: Rubber rodSRA grip coefficient: 0.50SRB grip coefficient: 0.32

BENEFITS:

- Exceptional grip on slippery floors
- Safe travel to the workplace
- Adapts to any type of surface and any type of shoe
- Hygienic and comfortable solution
- Ease of use and maintenance
- Anti-slip crampons designed to expel liquids and limit clogging
- Exceptional elongation capacity: 4 sizes cover all shoe sizes
- Rubber formula meets abrasion, tear and oil resistance standards
- Non-slip sole that leaves no marks on the floor

CARE AND STORAGE:

- Hand washable, leave to dry away from a heat source
- Store away from humidity and in a place not subject to temperature variations
- Do not use the overshoe below -25°

STANDARDS:

Complies with EU regulation 2016/425 relating to PPE (Personal Protective Equipment)

Complies with EN ISO 20347:2012 standard for work shoes that do not require protection against mechanical risks