

SPECIFICATIONS



ARTICLE

Designation : **NORDIC boot S3**

Code bobet :

17325 : S.39 | 17330 : S.44

17326 : S.40 | 17331 : S.45

17327 : S.41 | 17332 : S.46

17328 : S.42 | 17333 : S.47

17329 : S.43

Selling Unit : **pair**

Non-contractual pictures



CHARACTERISTICS

- Pull-up water resistant leather, lining :
 - *WingTex air tunnel textile
 - * Thinsulate, cold insulation
- AirToe Composite perforated safety toe cap with breathable membrane
- Removable Ergo Dry sole made of active carbons felt.
- Covering sole with polyurethane ascent on the front.
- Last : Natural Comfort 11 Mondopoint.
- SRC grip coefficient :
 - * Ceramic / water-detergent SRA : 0.45 flat shoe and 0.32 shoe inclined toward heel (7°)
 - * Steel/glycerin SRB : 0.44 flat shoe and 0.21 shoe inclined toward heel (7°)

DESCRIPTION :

- Upper :**
- Upper leather : Pull-up water resistant leather thickness 1.8/2.2 mm
 - Lining : Thinsulate and Wing Tex
 - Tab on the upper to easily put them on.
 - Steel toe cap : 200 joules

- Sole :**
- Assembly : Strobel.
 - Antistatic.
 - Comfort sole : dual density Polyurethane, dark grey.
 - Outsole : PU, light grey.
 - Comfort density : 0.50
 - Puncture resistant stainless steel midsole

STANDARDS :

In compliance with the European Regulation UE 2016/425 on personal protective equipment

In compliance with the European EN ISO 20345:2011 S3 CI SRC

With safety toe cap

S3 : Fundamental requirements + closed rear + anti-static + energy absorption in the heel + resistance to hydrocarbons + perforation resistance + material for water-repellent upper

CI : Thermal insulation against cold

SRC : Outsole slip resistance on ceramic and steel

Weight (Size 42) : 1.58 Kg / pair

