

SPECIFICATIONS

ARTICLE

Designation : **Schermer prodder**

Code bobet :

20622 : prodder

20623 : extension

Selling Unit : **Unit**

Non-contractual pictures

**CHARACTERISTICS**

- Tube with two round electrodes at one extremity. The electrical discharge happens only when pushing on the prodder.
- Length 270 mm. Tube diameter on the handle 50 mm
- Accessory : 75 cm extension (sold separately code Bobet 20623)

CHARACTERISTICS

BODY : Plastic IP65 - Net weight : 0.4 kg

POWER SUPPLY : 2 batteries LR 20 - Not supplied

EXIT/OUTLET TENSION : The device generates a high voltage of 5000V. Do not touch the electrodes ! When batteries are removed, a pulse may be generated by the residual charge. Note that this value, while configured to not cause irreversible damages, is very high, so that the device has to be used by staff advised in the treatment of animals in compliance with safeguarding of their welfare. A stealthy and non-continuous pressure on the button enables to shock while maintaining optimal battery from premature wear.

ELECTRODES : There are two metal rounded tips at one extremity to be applied on the animal so that it moves forward. The electrodes are placed at a sufficient distance to avoid electrical arcs.

ANIMAL WELFARE REGULATIONS :

In compliance with the regulation on animal welfare following the EC regulation 1099/2009 relative to animal protection when killed.

The prodder has to be used only for adult beef and adult pigs which refuse to move only when they the place to go forward. Shocks do not last more than 1 second, are properly spaced and are only done on the muscles of the hind limbs.

USE FORBIDDEN FOR PEOPLE WEARING A PACEMAKER

STANDARDS :

Complies with the following directives:

- EMC Directive: 2014/30/EU
- ROHS Directive: 2011/65/EU

Complies with the following standards:

- EN 55014-1:2017+A11:2020
- EN 55014-2:1997+AC:1997

- EN 50581:2012

