

SPECIFICATIONS



ARTICLE

<u>Designation</u>: **PUROFORT 04 green boot**

Code bobet:

8169: S.37 | 8171: S.41 | 8177: S.45 8172: S.38 | 8174: S.42 | 8178: S.46 8173: S.39 | 8175: S.43 | 8179: S.47 8170: S.40 | 8176: S.44 | 8180: S.48

<u>Selling Unit</u>: **pair** *Non-contractual pictures*





CHARACTERISTICS

- Without steel, sole resistant to petroleum products, anti-static, shock absorbing, thermal insulation.
- Composition: polyurethane
- Upper / sole color: green / brown
- Lining: polyamide covered with polyurethane
- SRC outsole for excellent grip on the ground, with a stud wear indicator and grooves to evacuate mud and water
- Boot upper: optimized foot support thanks to an optimized fit preventing the heel from slipping, light and flexible
- Use: agriculture, industries
- Resistance: manure, oils and fats, disinfectants, various chemicals

Material technology - PUROFORT®:

This polyurethane material exhibits exceptional characteristics and offers excellent performance in professional work applications. Using a unique process that produces a material that is light, durable, soft and flexible and offers thermal insulation down to -20 °C minimum, ideal for a whole day's work.

The Purofort® boot combines flexibility with a padded sole, making it very comfortable. The shock-absorbing heel prevents foot fatigue, reducing pressure on the knees and hips. Purofort® can last up to 3 times longer than a traditional safety boot. The economic benefit is therefore guaranteed.

STANDARDS:

Complies with EU regulation 2016/425 on personal protective equipment Complies with European standard EN ISO 20347:2012 O4 FO CI SRC

Without protective cap

04: anti-static shoes; heel energy absorption

FO: sole resistant to

hydrocarbons

CI: thermal insulation from cold

SRC: Non-slip sole on ceramic and steel floors

DESCRIPTION:

Weight (Size 42): Env. 1.46 Kg / pair

