

SPECIFICATIONS

ARTICLE

Designation : **ISO stainless steel female/female reducer**

Code bobet : *See table below*

Selling Unit : **Unit**




Non-contractual pictures

CHARACTERISTICS

Machined female/female reducer

Type : Gas/BSP

Stainless steel 316L



PMS of 64 bars up to DN50 and 40 bars beyond DN50 for water at ambient temperature

DN	F	Equivalence	G.	Equivalence	A (mm)	L (mm)	B (mm)	Weight (Kg)	Code Bobet
8-5	1/4"	8x13	1/8"	5x10	18	27	14	0.025	5540
12-8	3/8"	12x17	1/4"	8x13	22	30	17	0.045	5541
15-8	1/2"	15x21	1/4"	8x13	25	36	17	0.070	5542
15-12	1/2"	15x21	3/8"	12x17	25	36	21	0.070	5543
20-12	3/4"	20x27	3/8"	12x17	32	38	21	0.120	5544
20-15	3/4"	20x27	1/2"	15x21	32	38	27	0.110	5545
25-15	1"	26x34	1/2"	15x21	40	43	27	0.150	12332
25-20	1"	26x34	3/4"	20x27	40	43	33	0.150	5546
32-25	1"1/4	33x42	1"	26x34	50	45	42	0.240	5547
40-32	1"1/2	40x49	1"1/4	33x42	55	50	55	0.310	5548
50-32	2"	50x60	1"1/4	33x42	70	57	55	0.650	5549
50-40	2"	50x60	1"1/2	40x49	70	57	60	0.650	5550
65-50	2"1/2	66x76	2"	50x60	85	68	75	0.930	5551
80-65	3"	80x90	2"1/2	66x76	100	75	87	1.150	5552

Dimensional datas are subject to change