

SPECIFICATIONS



ARTICLE

Designation : **RESPONSE white shoe S2**

Code bobet : *See table below*

Selling Unit : **pair**



Non-contractual pictures

Code	Description	Code	Description	Code	Description
15331	S.35	15335	S.39	15339	S.43
15332	S.36	15336	S.40	15340	S.44
15333	S.37	15337	S.41	15341	S.45
15334	S.38	15338	S.42	15342	S.46
				15343	S.47
				15344	S.48

CHARACTERISTICS



- Lightweight shoe, comfortable, no side seams and no lace, antislip sole.
- AirToe Composite perforated safety toe cap with breathable membrane .
- Colour: white.
- Metal free
- RSC grip coefficient :
 - * Ceramic / water-detergent SRA : 0.45 flat shoe and 0.32 shoe inclined toward heel (7°)
 - * Steel/glycerin SRB : 0.44 flat shoe and 0.21 shoe inclined toward heel (7°)

DESCRIPTION :

- Upper :**
- New SAFETY DRY water repellent microfiber, white colour, thickness 2 mm
 - Lining : WingTex air tunnel textile.
 - Toe cap 200 joules.

The upper in New SAFETY DRY provides protection against unseen enemies such as bacteria and organic residues.

- Sole :**
- Assembly : Strobel.
 - Antistatic compact polyurethane sole
 - Insole : PU
 - Outsole: anti-abrasion and outstanding antiblock
- Removable WHITE ERGO DRY insole, in carbon felt active on cloth with breathable open cells. Anti-abrasion, antislip, anti-bacteria, antistatic and washable.
- Extra soft outsole with 90° spikes providing a better grip on difficult floors as well as on oily surfaces.

STANDARDS :

In compliance with the European Regulation UE 2016/425 on personal protective equipment

In compliance with the European standard EN ISO 20345:2011 S2 SRC

With safety toe cap

S2 : Fundamental requirements + anti-static + energy absorption in the heel + hydrocarbons-resistant contact sole
SRC : Outsole slip resistance on ceramic and steel

Weight (Size 42) : 0.89 Kg / pair

