

SPECIFICATIONS



ARTICLE

Designation: Shell FFP2 mask 3M

Code bobet : **11267**Selling Unit : **Unit**





Non-contractual pictures

CHARACTERISTICS

This 3M 8810 mask offers effective, lightweight and comfortable protection against dust. The two elastic straps and the nose clip allow a perfect fit to the face, thus avoiding the risk of leakage.

The mask is completely disposable: it requires no maintenance and has no spare parts

The following materials were used in the manufacture of this product:

Elastics: PolyisopreneNose clip: Aluminum

- Filter media/shell: Polypropylene/Polyester

- Nose foam: Polyurethane

APPLICATIONS:

Basic metallurgy, Public works, Chemicals (powders), Laboratories, Pharmaceutical industry

USAGE LIMITS:

This mask can be used as protection against solid aerosols, liquids whose liquid phase is water and non-volatile liquids for concentrations not exceeding 10 times the Average Exposure Value / Belgian Limit Value

PACKAGING:

Box of 20 pieces.

WARNING:

- The user must have received prior training in the proper use of the product.
- This product does not protect the wearer against gases, vapours, solvents encountered during cleaning operations. paint spraying or in atmospheres containing less than 19.5% oxygen.
- To be used only in suitably ventilated places and where the oxygen content is sufficient for the life.
- Do not use when the contaminant concentration presents an immediate danger to life.
- Leave the premises immediately if:
- * Breathing becomes difficult
- * Dizziness or other discomfort felt
- Never modify or "tinker" with this device.
- Non-observance of the instructions and precautions for use of this product, as well as non-compliance with instructions for continuous wearing of the mask during the entire period of exposure to the contaminant may reduce the effectiveness of the product and affect the health of the user, exposing him to serious disorders or putting his life in danger.



STANDARDS:

Complies with EU regulation 2016/425 relating to personal protective equipment (Category III)

Complies with European standard EN 149:2001 + A1:2009 FFP2 NR D

- * NR: use limited to one working day
- * D: clogging performance

