

SPECIFICATIONS

ARTICLE

Designation : **Swivel housing in stainless steel with plate**

Code bobet :

153 : Diam. 80 mm

154 : Diam. 100 mm

155 : Diam. 125 mm SP

156 : Diam. 160 mm

157 : Diam. 200 mm

Selling Unit : **Unit**

Non-contractual pictures



CHARACTERISTICS

Swivel clevis with plate

(PP = small stage and GP = large stage)

- Frame: plate and cap in AISI 304 stainless steel, corrosion resistant
- Central axis integrated into the plate cold riveted
- Pivoting performed by a double crown of greased balls
- Protection of the upper ball crown by plastic dust cover
- Compatible with NYLTEC wheel
- This type of mount is suitable for applications exposed to low stresses (max. 300kg), suitable for humid and corrosive environments
- max temperature of use: 80°C

Details	Height with wheels	Sun Int. Platinum	Axis dimension between mounting	Entrefourche	Rated load capacity	Code
For wheel D.80	108 mm	85 x 100 mm	80 x 50 mm	40 mm	200 kg	153
For wheel D.100	129 mm	85 x 100 mm	80 x 60 mm	45 mm	200 kg	154
For wheel D.125	156 mm	85 x 100 mm	80 x 60 mm	45 mm	220 kg	155
For wheel D.160	198 mm	110 x 140 mm	105 x 87 mm	60 mm	300 kg	156
For wheel D.200	241 mm	110 x 140 mm	105 x 87 mm	61 mm	300 kg	157