

SPECIFICATIONS

ARTICLE

Designation : Swivel housing in stainless steel with brake and plate

Code bobet :

9475 : Diam. 80 mm

163 : Diam. 100 mm

164 : Diam. 125 mm SP

165 : Diam. 150/160 mm

166 : Diam. 200 mm

Selling Unit : Unit

Non-contractual pictures



CHARACTERISTICS

Swivel clevis with brake, with plate

(PP = small plate)

- Frame: plate and cap in AISI 304 stainless steel, corrosion resistant
- Stainless steel brake pedal, adjustable double effect (wheel + swivel)
- Central axis integrated into the plate cold riveted
- Pivoting performed by a double crown of greased balls
- Protection of the upper ball crown by plastic dust cover
- Compatible with NYLTEC wheel
- This type of mount is suitable for applications exposed to low stresses (max. 300kg), suitable for humid and corrosive environments

Details	Height with wheels	Sun Int. Platinum	Axis dimension between mounting	Entrefourche	Rated load capacity	Code
For wheel D.80	109 mm	85 x 105 mm	80 x 60 mm	42 mm	120 kg	9475
For wheel D.100	129 mm	85 x 100 mm	80 x 60 mm	45 mm	200 kg	163
For wheel D.125	156 mm	85 x 100 mm	80 x 60 mm	45 mm	220 kg	164
For wheel D.150/160	198 mm	110 x 140 mm	105 x 87 mm	60 mm	300 kg	165
For wheel D.200	241 mm	110 x 140 mm	105 x 87 mm	60 mm	300 kg	166