

SPECIFICATIONS

**ARTICLE**

Designation : **TILSATEC 50-6121 glove**

Code bobet :

23857 : S7/S

23858 : S8/M

23712 : S9/L

23713 : S10/XL

23791 : S11/XXL

Selling Unit : **pair**

Non-contractual pictures

**CHARACTERISTICS**

- Sandy foam nitrile palm coated glove with thumb reinforcement
- Knitted wrist
- Color : black lining / black coating
- Gauge : 10
- length: 230 à 270 mm
- Ultra cut resistance of level F
- Rhino Yarn™ cut resistant technology
- Heat contact protection : EN407, level 1
- Thumb-index reinforcement for a better resistance while doing heavy work
- High level of abrasion resistance and great durability
- Breathability : 360°
- "DMF" undetectable levels

APPLICATIONS :

Metal/stamping fabrication , glass fabrication and glazing assembly, transport, industrial production, construction, waste handling / recycling

PACKAGING :

12 pairs in a polyethylene bag, 120 pairs in a box

STANDARDS :


Complies with EU regulation 2016/425 relating to personal protective equipment (Category II)

Complies with European standards:

- General requirements: EN ISO 21420:2020
- Mechanical risk: EN 388:2016 + A1:2018: 4X43F
- Thermal risk: EN 407:2020 X1XXXX



EN ISO 21420 :
2020 Cat.II



EN388:2016 + A1:
2018- 4X43F



EN 407 : 2020
X1XXXX