

SPECIFICATIONS

**ARTICLE**Designation : **ULISSE white shoe S2**Code bobet : *See table below*Selling Unit : **pair**

Non-contractual pictures

Code	Description	Code	Description	Code	Description
24986	S36	24989	S39	24992	S42
24987	S37	24990	S40	24993	S43
24988	S38	24991	S41	24994	S44
				24995	S45
				24996	S46

CHARACTERISTICS

White shoe HAUTE ULISSE S2 special for the food industry and communities

- Comfortable high shoe with laces, non-slip sole
- Steel toe cap 200 joules
- Color: white
- Adhesion coefficient:
 - * Ceramic + detergent solution – tip (7° inclination) 0.40
 - * Ceramic + detergent solution – heel (7° inclination) 0.35
 - * SR: ceramic + glycerin – tip (7° inclination) 0.27
 - * SR: ceramic + glycerin – heel (7° inclination) 0.33
- Weight (P.42): 1030 g / pair

DESCRIPTION :

Upper : - NEWTECH water-repellent microfibre, white colour, 1.8 mm thick
 - Lining: Breathable blue fabric
 - Polyester lace

Sole : - Antistatic, absorbent and resistant insole
 - Removable EVANIT scented insole in EVA/nitrile
 - Single density polyurethane sole
 - Resistance to abrasion and hydrocarbons

STANDARDS :

Complies with EU Regulation 2016/425 on personal protective equipment

Complies with European standard EN ISO 20345:2022 S2 FO SR

With protective toe cap

S2: fundamental requirements + antistatic + Energy absorption at the heel + Water resistance to upper materials

FO: Resistance to hydrocarbons

SR: Slip resistance (ceramic floor + oil)

