

SPECIFICATIONS

ARTICLE

Designation : **NYLTEC wheel with double ball bearing**

Code bobet :

17 : 100 x 12 mm

18 : 130 x 20 mm

20 : 150 x 20 mm

9449 : 160 x 20 mm

22 : 200 x 20 mm

Selling Unit : **Unit**

Non-contractual pictures



CHARACTERISTICS

Polyamide wheel, hub with ball bearing, medium load

- One-piece injected wheel
- High resistance to shocks, wear and corrosion
- Good resistance to oils and hydrocarbons, brine, lactic acids and several chemicals
- Resistance to temperature : -30°C to +80°C
- Low starting effort

APPLICATIONS :

- Especially recommended for food industries and static uses
- Unsuitable for strong mineral acids and concentrated organic ones.

Wheel Diameter	Tread width	Bore	Hub length	Load capacity	Weight	Code
100 mm	40 mm	12 mm	45 mm	250 kg	0,220 kg	17
125 mm	40 mm	20 mm	60 mm	350 kg	0,495 kg	18
150 mm	45 mm	20 mm	60 mm	400 kg	0,620 kg	20
160 mm	45 mm	20 mm	60 mm	450 kg	0,720 kg	9449
200 mm	50 mm	20 mm	60 mm	500 kg	0,920 kg	22