

SPECIFICATIONS

ARTICLE

Designation : **NYLTEC wheel with smooth hub**

Code bobet :

1 : 80 x 12 mm | 8 : 160 x 20 mm
 2 : 100 x 12 mm | 9 : 160 x 25 mm
 4 : 125 x 20 mm | 10 : 200 x 20 mm
 6 : 150 x 20 mm | 11 : 200 x 25 mm
 7 : 150 x 25 mm

Selling Unit : **Unit**

Non-contractual pictures



CHARACTERISTICS

Polyamide wheel, smooth hub, medium load

- One-piece injected wheel
- High resistance to shocks, wear and corrosion
- Good resistance to oils and hydrocarbons, brine, lactic acids and several chemicals
- Resistance to temperature : -30°C to +80°C
- Low starting effort

APPLICATIONS :

- Especially recommended for food industries and static uses
- Unsuitable for strong mineral acids and concentrated organic ones.

Wheel Diameter	Tread width	Bore	Hub length	Load capacity	Weight	Code
80 mm	35 mm	12 mm	40 mm	150 kg	0,100 kg	1
100 mm	40 mm	12 mm	45 mm	250 kg	0,180 kg	2
125 mm	40 mm	20 mm	60 mm	300 kg	0,260 kg	4
150 mm	45 mm	20 mm	60 mm	350 kg	0,320 kg	6
150 mm	45 mm	25 mm	60 mm	350 kg	0,320 kg	7
160 mm	45 mm	20 mm	60 mm	380 kg	0,420 kg	8
160 mm	45 mm	25 mm	60 mm	380 kg	0,420 kg	9
200 mm	50 mm	20 mm	60 mm	450 kg	0,660 kg	10
200 mm	50 mm	25 mm	60 mm	450 kg	0,660 kg	11