

SPECIFICATIONS

ARTICLE

Designation : **NYLTEC wheel with narrow smooth hub**

Code bobet :

9459 : 100 x 12 mm | 14 : 125 x 20 mm

13 : 125 x 12 mm | 15 : 150 x 15 mm

6537 : 125 x 15 mm | 16 : 150 x 20 mm

Selling Unit : **Unit**

Non-contractual pictures



CHARACTERISTICS

Polyamide wheel, narrow smooth hub, medium loads

- One-piece injected wheel
- High resistance to impact, wear and corrosion
- Very good resistance to oils and hydrocarbons, brine, lactic acid and many chemical agents
- Temperature resistance: -30 to + 80 °C
- Low starting effort

USES:

- Particularly suitable for food industries and for static uses
- Unsuitable in the presence of strong mineral acids and concentrated organic

Wheel Diameter	Tread width	Bore	Hub length	Load capacity	Weight	Code
100 mm	30 mm	12 mm	40 mm	175 kg	0,140 kg	9459
125 mm	40 mm	12 mm	45 mm	250 kg	0,220 kg	13
125 mm	40 mm	15 mm	45 mm	250 kg	0,220 kg	6537
125 mm	40 mm	20 mm	45 mm	250 kg	0,220 kg	14
150 mm	40 mm	15 mm	45 mm	350 kg	0,320 kg	15
150 mm	45 mm	20 mm	45 mm	350 kg	0,320 kg	16