

SPECIFICATIONS

ARTICLE

Designation : **SUPER NYLTEC wheel with smooth hub**

Code bobet :

24 : 75 x 12 mm | 29 : 150 x 25 mm

25 : 100 x 12 mm | 30 : 200 x 20 mm

26 : 125 x 20 mm | 31 : 200 x 25 mm

28 : 150 x 20 mm

Selling Unit : **Unit**

Non-contractual pictures



CHARACTERISTICS

Polyamide wheel, smooth hub, heavy load

- One-piece injected wheel
- High resistance to shocks, wear and corrosion
- Good resistance to oils and hydrocarbons, brine, lactic acids and several chemicals
- Resistance to temperature : -30°C to +80°C
- Low starting effort

APPLICATIONS :

- Especially recommended for food industries and static uses
- Unsuitable for strong mineral acids and concentrated organic ones.

Wheel Diameter	Tread width	Bore	Hub length	Load capacity	Weight	Code
75 mm	35 mm	12 mm	40 mm	250 kg	0,100 kg	24
100 mm	38 mm	12 mm	45 mm	400 kg	0,200 kg	25
125 mm	40 mm	20 mm	60 mm	600 kg	0,350 kg	26
150 mm	45 mm	20 mm	60 mm	700 kg	0,580 kg	28
150 mm	45 mm	25 mm	60 mm	700 kg	0,550 kg	29
200 mm	50 mm	20 mm	60 mm	1000 kg	0,950 kg	30
200 mm	50 mm	25 mm	60 mm	1000 kg	0,920 kg	31